



IP COMM, AV, EPABX, INTERCOMS & MORE



www.v-proworld.com





TECHNICAL SPECIFICATIONS

- Micro Controller based
- Insertion Loss-Less than 1db (Extn. To Trunk)
- Trunk loop resistance 1200 Ohms
- Cross talk better than 70db.
- Input Power AC 220V 50Hz
- Power consumption less than 20 watt
- Ext. Voltage 40V DC
- Cabling Single Pair

EXTENSION FUNCTION

- Auto Call Back In Busy Jn/ext.
- Class Of Service :
 - * Intercom / Local / Std / Isd
- Caller Id Dtmf
- Call Hold
- Call Toggle
- Call Pickup-common / Selective
- Conference (3 Party)
- Do Not Disturb
- Flash Time Programable
- Alarm
 - * One Time Alarm
 - * Three Schedule Alarm
- 9 Busy Hunting Group
- Call Forward
- Barge In With Beep
- Executive / Normal / Cordless Ring
- Flexible Numbering
- Monitor
- Call Transfer After Consult / Without Consult

SYSTEM CONTROL

- Password Protected
- Built in RTC
- Bulk Programming
- Paging Port
- Remote Programming
- Power Failure Trunk Transfer
- Inbuilt Relay Port
- Number / Date / Time Display on FND
- Relay Action (Manual / Auto)
 - * Elect Gadget & EM-Lock
 - * 10 Set of Time for Relay
 - * Automatic On / OFF with time duration
- 100 Global Number
- RMOH Recordable music on hold

TRUNK FUNCTION

- Incoming
 - * Round Robin Ring
 - * Simultaneous Ring
 - * Delayed Simultaneous
- Direct Inward Dialing (DID)
 - * DID By Extension Number
- VDC
 - * Welcome
 - * Ext. Busy
 - * Wrong Number
- Day / Night Mode (Auto / Manual)
- Access Group for Trunk
- Caller ID FSK-DTMF
- DTMF Dialing
- Hot Line
- Last No. Redial
- Linear / Rotational / Selective Access
- Reserve Junction Line
- Selective Trunk Barring
- Auto Shut Dynamic Lock
- Feature Enable / Disable
- Jn. Tie Line Count

HOTEL FUNCTION

- Room No. Wise Extn. No.
- Floor Wise Room Service
- Single Digit Access to Service Extn.
- Guest Extension Grouping
- Extension to Extension Call Barring / Open Group Function
 - * Individual
 - * Guest
 - * Service
- 9 Busy Hunting Group
- FND Display
- 9 Different Call Back up Group
- 10 Emergency Calling Code



MODELS AND DIMENSIONS

Model	Dimensions (cm)		
	W	H	D
104	14	23	6
108 / 208 / 308 / 210 / 214 / 312 / 316	21	32	5
24 P	28	26	12
40 P	28	40	11
72 P	28	47	16